

## TECHNICAL DATA

Slides per basket:	Up to twenty
Containers for reagents:	Four
Rinse water bath :	One with overflow. Optional bottom drain can be installed.
Drying container:	Warm air flow (60°C).
Programming:	Time to dip the basket in each container. During this time, resting periods and shaking periods. Time to maintain the basket on top of each container after dipping.
Number of programs:	The memory can store up to ten programs
Positions per program:	The basket can go to ten different positions. At each of them the total dipping time, resting and shaking, and drain over the container can be selected.
Mains:	100/240 V, 50/60 Hz, 250 W

Code	Dimensions (LxWxH)	Weight	Unit	Price
FRO5303	700x440x400m	23kg	Each	\$14,500
	Basic unit includes one slide basket and four plastic containers with lid.			



Advancing Australia in Science

# POLY STAINER



**Lomb Scientific Pty Ltd**

26 Atkinson Rd (PO Box 2223) Taren Point 2229 NSW

NSW: 02-8536 6222 VIC 03-9371 0000 QLD 07-3850 8466 SA 08-8464 0299

WA 08-9358 1844 EMAIL sales@lomb.com.au www.lomb.com.au

**Protected electronic**

All the electronic circuit and electrical components are built in an elevated bridge. No splashing can damage them.



**Removable container tray**

The stainless steel container tray, can be easily removed and replaced without any tool.



**Quick drain system**

As optional accessory the quick drain system allows to empty out the water container from the bottom. In the normal situation the water overflows.



Arrange the slides in the basket and hang it on the lift.



Perform or select a program using the symbolic display/keyboard.



The basket runs automatically to all the selected positions, at the times and shaking required.



Once the program finished, take the basket at the rest position.

